















Certified for
HP Latex Inks



Материал		DIN 60001	100 % полиэстер
Основа		DIN ISO 9354	тканое полотно
Плотность		DIN EN ISO 2286-2	120 г/м ²
Огнестойкость		B-s1,d0*, ÖNORM A3800, NFPA 701	есть
Применение			внутри
Ширина		DIN EN ISO 2286-1	макс. 510 см / 201 дюйм (см.на сайте)
Печатная сторона			ширина < 3 м: печатная сторона снаружи ширина > 3 м: печатная сторона внутри
Длинна рулона			40 - 150 ± 0,5 м
Тип чернил		  	все типы сольвентных чернил, УФ, латексные чернила

Преимущества

- доступна в большой ширине
- быстро разглаживается
- растягивается
- мягкая
- грязеотталкивающая
- холодная резка

Применение

- лайтбокс с подсветкой
- натягивающаяся конструкция

* permits the classification into the category M1



All details are nominal values and are subject to change within usual tolerances (± 5 %). The information provided in this document is based on current knowledge and experience. They do not exempt a manufacturer/processor from carrying out their own tests and trials as their in-house handling and manufacturing processes can have a significant range of influences on outcomes. Application, utilisation and processing of products is taking place outside of our control and are therefore the sole responsibility of the manufacturer/processor. date: 01/2020