



Certified for
HP Latex Inks



Материал		DIN 60001	100 % полиэстер
Основа		DIN ISO 9354	тканое полотно
Плотность		DIN EN ISO 2286-2	200 г/м ²
Огнестойкость		DIN 4102 B1, ÖNORM A3800, NFPA 701, CA 1237	есть
Применение			внутри, снаружи (краткосрочно)
Ширина		DIN EN ISO 2286-1	макс. 310 см / 122 дюйм (см.на сайте)
Печатная сторона			ширина < 3 м: печатная сторона снаружи ширина > 3 м: печатная сторона внутри
Длина рулона			30 - 50 ± 0,5 м
Тип чернил		  	все типы сольвентных чернил, УФ, латексные чернила

Преимущества

- быстро разглаживается
- водоотталкивающая
- легко очищается
- грязеотталкивающая
- холодная резка

Применение

- подсветка с лицевой стороны
- натягивающаяся конструкция

* not for outdoor use



All details are nominal values and are subject to change within usual tolerances ($\pm 5\%$). The information provided in this document is based on current knowledge and experience. They do not exempt a manufacturer/processor from carrying out their own tests and trials as their in-house handling and manufacturing processes can have a significant range of influences on outcomes. Application, utilisation and processing of products is taking place outside of our control and are therefore the sole responsibility of the manufacturer/processor. date: 01/2020